

AMENDMENT(S) TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in this application:

Listing of Claims:

Claims 1-24 (Canceled)

25. (Currently amended) A method for performing at least one of detecting a presence, determining a spatial distribution, and quantifying an amount of at least ~~[[a]]~~ one chemical species in a surrounding medium, said method comprising:

(1) providing a capillary having two opposed ends and a wall that is permeable to said at least one chemical species ~~at a location where said chemical species is suspected to be present;~~

(2) delivering at least one fluid medium into a space inside said capillary, said fluid medium comprising a reagent that is capable of undergoing a selective interaction with said chemical species permeating through said wall to produce a product having a detectible characteristic;

(3) providing at least one detector having a sensing element operable to detect said characteristic;

(4) positioning the capillary containing the fluid medium in the surrounding medium at a location where said chemical species is suspected to be present;

(4) (5) allowing said at least one fluid medium to reside in said capillary without being removed and allowing said chemical species to permeate through said wall of said capillary and into said fluid medium in a region of the fluid medium corresponding to the location in the surrounding medium where the chemical species is present;

(5) (6) then transferring a content of said capillary to said sensing element of said detector after a permeation of said chemical species into said capillary, said content comprising said fluid medium;

(6) (7) detecting and measuring a magnitude of said characteristic;

(7) (8) measuring a time at which said characteristic is detected and measured and determining the length of travel time for the region of the fluid medium containing the chemical species to reach the detector; and

(8) (9) relating said magnitude of said characteristic to said amount of said chemical species and relating said travel time to a spatial distribution of said product within said capillary and the corresponding spatial distribution of said chemical species within the surrounding medium.

26. (Original) The method according to claim 25, wherein said detector employs a method of detection selected from the group consisting of optical, spectroscopic, electrochemical, gravimetric, and mass spectrometric methods.

27. (Original) The method according to claim 26, wherein said optical method is selected from the group consisting of refractive index measurement and light scattering.

28. (Original) The method according to claim 26, wherein said spectroscopic method is selected from the group consisting of measurements of UV-VIS electronic absorbance, Raman spectra, luminescence spectra, infrared spectra, and near-infrared spectra.

29. (Currently amended) A method for performing at least one of detecting a presence, determining a spatial distribution, and quantifying an amount of at least [[a]] one chemical species in a surrounding medium, said method comprising:

(1) providing a capillary having two opposed ends and a wall that is permeable to said at least one chemical species ~~at a location where said chemical species is suspected to be present;~~

(2) delivering at least one fluid medium into a space inside said capillary, said fluid medium comprising a reagent that is capable of undergoing a selective interaction with said chemical species permeating through said wall to produce an optically detectable product;

(3) providing at least one detector having a sensing element for detecting said optically detectable product;

(4) positioning the capillary containing the fluid medium in the surrounding medium at a location where said chemical species is suspected to be present;

(4) (5) allowing said at least one fluid medium to reside in said capillary without being removed and allowing said chemical species to permeate through said wall of said capillary and into said fluid medium in a region of the fluid medium corresponding to the location in the surrounding medium where the chemical species is present and selectively interact with said reagent to produce an optically detectable product;

(5) (6) then transferring, after said selective interaction, a content of said capillary to said sensing element of said detector, said content comprising said optically detectable product;

(6) (7) detecting and measuring a magnitude of an optical signal resulting from a presence of said optically detectable product;

(7) (8) measuring a time at which said optical signal is detected and measured and determining the length of travel time for the region of the fluid medium containing the chemical species to reach the detector; and

(8) (9) relating said magnitude of said optical signal to an amount of said chemical species, and relating said travel time to a spatial distribution of said optically detectable product within said capillary and the corresponding spatial distribution of said chemical species within the surrounding medium.

30. (Original) The method according to claim 29, wherein said optical signal is selected from the group consisting of absorbance and intensity of emission of EM radiation having a wavelength in a range from about 100 nm to about 1 mm.

31. (Previously presented) The method according to claim 29, wherein said capillary comprises a polymeric material selected from the group consisting of expanded polytetrafluoroethylene, poly(vinyl chloride), poly(vinyl alcohol), polyurethane, polyolefins, polycarbonate, polystyrene, polyamide, poly(vinylidene fluoride), polyarylsuphones, polyacrylonitrile, polyether, poly(ether thioether), poly(methyl methacrylate), polyvinylpyrrolidone, polysiloxane, copolymer of perfluorosulfonic acid and polytetrafluoroethylene, random copolymer of tetrafluoroethylene and perfluoro-2,2-dimethyl-1,3-dioxole, copolymer of perfluorosulfonic acid and polytetrafluoroethylene, random copolymer of tetrafluoroethylene and perfluoro-2,2-dimethyl-1,3-dioxole, copolymers thereof, and blends thereof.

32. (Previously presented) The method according to claim 29, wherein said capillary comprises a polymeric material deposited on a porous solid substrate; said polymeric material being selected from the group consisting of expanded polytetrafluoroethylene, poly(vinyl chloride), poly(vinyl alcohol), polyurethane, polyolefins, polycarbonate, polystyrene, polyamide, poly(vinylidene fluoride), polyarylsuphones, polyacrylonitrile, polyether, poly(ether thioether), poly(methyl methacrylate), polyvinylpyrrolidone, polysiloxane, copolymer of perfluorosulfonic acid and polytetrafluoroethylene, random copolymer of tetrafluoroethylene and perfluoro-2,2-dimethyl-1,3-dioxole, copolymer of perfluorosulfonic acid and polytetrafluoroethylene, random

copolymer of tetrafluoroethylene and perfluoro-2,2-dimethyl-1,3-dioxole, copolymers thereof, and blends thereof.

33. (Original) The method according to claim 32, wherein said porous solid substrate is a porous glass capillary.

34. (Original) The method according to claim 31, wherein said capillary is porous and has pore size in a range from about 1 nm to about 200 nm.

35. (Original) The method according to claim 34, wherein said capillary preferably has pore size in a range from about 1 nm to about 50 nm.

36. (Original) The method according to claim 31, wherein said capillary has an inner diameter in a range from about 2 micrometers to about 2 mm.

37. (Previously presented) The method according to claim 31, wherein said inner diameter is in a range from about 0.1 mm to about 1.5 mm.

38. (Original) The method according to claim 31, wherein said capillary has a wall thickness in a range from about 10 micrometers to about 200 micrometers.

39. (Previously presented) The method according to claim 38, wherein said wall thickness is in a range from about 10 micrometers to about 150 micrometers.

40. (Original) The method according to claim 29, wherein said chemical species is selected from the group consisting of halogenated hydrocarbons, polynitroaromatic hydrocarbons, mono-substituted benzene, aromatic aldehydes, aromatic amines, and mixtures thereof.

41. (Original) The method according to claim 40, wherein said halogenated hydrocarbons are trichloroethylene, trichloroethane, chloroform, bromoform, chlorodibromomethane, and bromodichloromethane.

42. (Original) The method according to claim 40, wherein said polynitroaromatic hydrocarbons are 1,3,5-trinitrobenzene; 2,4,6-trinitrobiphenyl; 2,3',4,5',6-pentanitrobiphenyl; 2,2',4,4',6,6'-hexanitrobiphenyl; 2,4,6-trinitrotoluene; 2,2',4,4',6,6'-hexatrinitrobiphenyl; 2,2',4,4',6,6'-hexanitrostilbene; 2,2',4,4'-tetranitrobiphenyl; 3,3',5,5'-tetranitrobiphenyl; 2,2',6,6'-tetranitrobiphenyl; 1,4,5,8-tetranitronaphthalene; 1,3-dinitrobenzene; 2-ethoxy-1,3,5-trinitrobenzene; 2-methyl-1,3-dinitrobenzene; 2,4-dimethyl-1,3-dinitrobenzene; and mixtures thereof.

43. (Original) The method according to claim 40, wherein said mono-substituted benzene has a formula of Ar-X, wherein Ar is a phenyl radical and X is a radical selected from the group consisting of $-\text{CH}_3$, $-\text{OCH}_3$, $-\text{C}_6\text{H}_5$, $-\text{SCH}_3$, and $-\text{SC}_6\text{H}_5$.

44. (Original) The method according to claim 40, wherein said aromatic aldehydes are benzaldehyde, 1-naphthaldehyde, 9-anthraldehyde, 4-dimethylaminocinnamaldehyde, 2-nitrobenzaldehyde, and 4-nitrobenzaldehyde.

45. (Original) The method according to claim 40, wherein said aromatic amines are pyridine and alkyl-substituted pyridine.

46. (Currently amended) A method for performing at least one of detecting a presence, determining a spatial distribution, and quantifying an amount of at least $[[a]]$ one chemical species in a surrounding medium, said method comprising:

(1) providing a capillary having two opposed ends and a wall that is permeable to at least one chemical species ~~at a location where said chemical species is suspected to be present;~~

(2) delivering at least one fluid medium comprising at least one reagent into a space inside said capillary, said at least one reagent being capable of undergoing a selective interaction with said chemical species to yield at least one optically detectable product said fluid medium

comprising a reagent that is capable of undergoing a selective interaction with said chemical species permeating through said wall to produce an optically detectable product;

(3) providing at least one detector having a sensing element for detecting said at least one optically detectable interaction product;

(4) positioning the capillary containing the fluid medium in the surrounding medium at a location where said chemical species is suspected to be present;

(4) (5) allowing said at least one fluid medium to reside in said capillary without being removed and allowing said chemical species to permeate through said wall of said capillary and into said fluid medium in a region of the fluid medium corresponding to the location in the surrounding medium where the chemical species is present and react with said reagent to yield said at least one optically detectable product;

(5) (6) then transferring, after said reaction, a content of said capillary to said sensing element of said detector, said content comprising said optically detectable product;

(6) (7) detecting and measuring a magnitude of an optical signal resulting from a presence of said optically detectable product;

(7) (8) measuring a time at which said optical signal is detected and measured and determining the length of travel time for the region of the fluid medium containing the chemical species to reach the detector; and

(8) (9) relating said magnitude of said optical signal to said amount of said chemical species and relating said travel time to a spatial distribution of said optically detectable product

within said capillary and the corresponding spatial distribution of said chemical species within the surrounding medium; and

wherein said capillary comprises a polymeric material selected from the group consisting of expanded polytetrafluoroethylene, poly(vinyl chloride), poly(vinyl alcohol), polyurethane, polyolefins, polycarbonate, polystyrene, polyamide, poly(vinylidene fluoride), polyarylsulphones, polyacrylonitrile, polyether, poly(ether thioether), poly(methyl methacrylate), polyvinylpyrrolidone, polysiloxane, copolymer of perfluorosulfonic acid and polytetrafluoroethylene, random copolymer of tetrafluoroethylene and perfluoro-2,2-dimethyl-1,3-dioxole, copolymers thereof, and blends thereof;

said detector is capable of quantitatively relating an optical signal resulting from a presence and an amount of said at least one optically detectable product to said presence and said amount of said chemical species outside said capillary;

and said optical signal is selected from the group consisting of absorbance and emission of EM radiation having a wavelength in a range from about 100 nm to about 1 mm.

47. (Original) The method according to claim 46, wherein said chemical species is selected from the group consisting of halogenated hydrocarbons, polynitroaromatic hydrocarbons, mono-substituted benzene, aromatic aldehydes, aromatic amines, and mixtures thereof.

48. (Previously presented) The method according to claim 29, further comprising detecting a presence of said chemical species in a predetermined environment, determining a spatial distribution of said chemical species in the predetermined environment, and quantifying an amount of said chemical species in the predetermined environment.

49. (Previously presented) The method according to claim 48, wherein said environment is soil.

50. (Previously presented) The method according to claim 29, further comprising detecting a presence and quantifying products of a chemical synthesis that is conducted in a combinatorial chemistry experiment.